

CERTIFICATE OF COMPLIANCE

Certificate Number E353501
Report Reference E353501-2013-08-07
Date 2021-October-28

Issued to: BARTEC F.N. S.R.L.
Via Mario Pagano 3
Trezzano S/Naviglio MI 20090 IT

**This is to certify that
representative samples of**

OUTLET AND JUNCTION BOXES FOR USE IN ZONE
CLASSIFIED HAZARDOUS LOCATIONS

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: Refer to the addendum page for standards

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E353501
Report Reference E353501-2013-08-07
Date 2021-October-28

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

MODELS

USL - Junction and Pull Boxes for use in Class I, Zone 1, AEx d IIC; Zone 21, AEx tb IIIC T150°C
IP66 Hazardous Locations

Model GUA; followed by 14, 24, 16, 26, 36, 17, 27, 37, 47, 59, or 69; followed by .C, .L, .T, .X, .B, .D, .Y, .M, .W, or .J

Model GUAY; followed by 14, 24, 16, 26, 36, 17, 27, 37, 47, 59, or 69

CNL - Junction and Pull Boxes for use in Ex d IIC; Class II, Groups E, F, and G Hazardous Locations

Model GUA; followed by 14, 24, 16, 26, 36, 17, 27, 37, 47, 59, or 69; followed by .C, .L, .T, .X, .B, .D, .Y, .M, .W, or .J

Model GUAY; followed by 14, 24, 16, 26, 36, 17, 27, 37, 47, 59, or 69

STANDARDS

UL 60079-0 Explosive Atmospheres – Part 0: Equipment – General Requirements


UL 60079-1 Explosive Atmospheres – Part 1: Equipment Protection by Flameproof Enclosures
“d”

ISA 60079-31:2009 Electrical Apparatus for Explosive Atmospheres – Part 31: Equipment Dust
Ignition Protection by Enclosure “t”

CAN/CSA C22.2 No. 60079-0:11 Explosive Atmospheres – Part 0: Equipment – General
Requirements

CAN/CSA C22.2 No. 60079-1:11 Explosive Atmospheres – Part 1: Equipment Protection by
Flameproof Enclosures “d”

CAN/CSA C22.2 No. 60079-31:12 Electrical Apparatus for Explosive Atmospheres – Part 31:
Equipment Dust Ignition Protection by Enclosure “t”



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

