

TC26ex-NI Touch Computer

Accessories











It is absolutely necessary to use original accessories from BARTEC!



Accessories for use in hazardous areas

Accessories are approved for:

- UL: Class I,II, III Div 2 (E321557)



Standard battery

Description	– certified in combination with TC26 ^{ex} -NI	
	– Lithium-ion battery 3.85 V/3400 mAh (13.09 Wh)	
	May only be changed and charged outside hazardous areas!	
Order no.	B7-A2Z0-0075	



Extended battery

Description	- certified in combination with TC26ex-NI
	- Lithium-ion battery 3.85 V/5260 mAh (20.25 Wh)
	May only be changed and charged outside hazardous areas!
Order no.	B7-A2Z0-0080



Hand strap


Description	– certified in combination with TC26 ^{ex} -NI
	– only for Touch Computer without scan handle
Order no.	B7-A2Z0-0079





Scan handle

Description	– certified in combination with TC26 ^{ex} -NI
	- simple assembly and disassembly without tools
	- does not block camera or other feature
	– only usable without hand strap
	– charging with mounted scan handle possible
	May only be changed outside hazardous areas!
Order no.	B7-A2Z0-0078



Screen protector

Description	- Certified in combination with TC26ex-NI
	-1 piece
	May only be changed outside hazardous areas!
Order no.	B7-A2Z0-0076



Stylus

Description	-Suitable for TC26ex-NI
	- passive stylus
	- with spiral cable
	-3 pieces
	May only be changed outside hazardous areas!
Order no.	17-S1Z0-0008



Accessories for use outside hazardous areas



4-slot battery charging station

Description	- Charging four batteries	
	 Charging Standard battery and Extended battery 	
	- Charging display via LED	
Scope of delivery	4-slot battery charging station	
Also required	(not included in the delivery)	
	– Power supply with DC connecting cable	
	- AC power cable	
Order no.	G7-A0Z0-0054	



Base station

Description	- Charging the Touch Computer - Communication via USB	
Scope of delivery	Base station	
Also required	(not included in the delivery) - Power supply with DC connecting cable	
	- AC power cable	
	- USB cable for data communication (03-9919-0013)	
Order no.	G7-A0Z0-0052	



Power supply with DC connecting cable

Description	– for 4-slot battery charging station and Base station
	- Input voltage: AC 100 to 240 V
	– Output voltage: DC 12 V/4.16 A/50 W
Order no.	G7-A0Z0-0023





AC power cable

Description	-3-wire	
	-country-specific	
Order no.	Version: US + Canada	G7-A0Z0-0024
	Version: EU + APAC	G7-A0Z0-0026
	Please purchase the requ specific cables in the resp	,



Wall Charger

Description	– Input voltage: AC 10	– Input voltage: AC 100 to 240 V	
	- Output voltage: DC 5	5 V/2.5 A/12.5 W	
Order no.	Version: US	G7-A0Z0-0056	
	Version: EU	G7-A0Z0-0057	
Also required	(not included in the delivery)		
	- USB cable (G7-A0Z0	-0046)	



USB cable

Description	- Connection between Touch Computer and base station for data communication
	- USB (A) to micro USB (B)
	-Length:1m
Order no.	03-9919-0013



USB cable

Description	- Connection between Touch Computer and PC for data communication
	 Connection between Touch Computer and Wall Charger for charging
	- USB (A) to USB (C)
	– Length: 1.5 m
Order no.	G7-A0Z0-0046