

Translation

EU-Type Examination Certificate

Equipment intended for use in potentially explosive atmospheres
Directive 2014/34/EU

EU-Type Examination Certificate Number: **BVS 16 ATEX E 129 X**

Product: **Flameproof electric motor type 5KT** 250 */***

Manufacturer: **BARTEC VARNOST, d.o.o.**

Address: **Cesta 9. avgusta 59, 1410 Zagorje ob Savi, Slovenia**

This product and any acceptable variations thereto are specified in the appendix to this certificate and the documents referred to therein.

DEKRA EXAM GmbH, Notified Body number 0158, in accordance with Article 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014, certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in the confidential Report No. BVS PP 18.2053 EU.

Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN 60079-0:2012 + A11:2013	General requirements
EN 60079-1:2014	Flameproof enclosure "d"
EN 60079-7:2015	Increased Safety "e"
EN 60079-31:2014	Protection by Enclosure "t"

If the sign "X" is placed after the certificate number, it indicates that the product is subject to the Special Conditions for Use specified in the appendix to this certificate.

This EU-Type Examination Certificate relates only to the design and construction of the specified product. Further requirements of the Directive apply to the manufacturing process and supply of this product. These are not covered by this certificate.

The marking of the product shall include the following:

	II 2G Ex db IIC T* Gb	or	Ex db eb IIC T* Gb
	II 2G Ex db IIB T* Gb	or	Ex db eb IIB T* Gb
	II 2D Ex tb IIIC T* °C Db	or	
	I M2 Ex db I Mb	or	Ex db eb I Mb

*) see parameters

DEKRA EXAM GmbH
Bochum, 2018-04-17

Signed: Jörg Koch

Signed: Dr Franz Eickhoff

Certifier

Approver

13 **Appendix**

14 **EU-Type Examination Certificate**
BVS 16 ATEX E 129 X

15 **Product description**

15.1 **Subject and type**

Flameproof electric motor type 5 KT** 250 */*

Asterisk Description

- | | |
|-------|--|
| 1 | Explosion Group:
C IIC / IIIC
B IIB |
| 2 | Application area
R: Engine for use in mining operations (Group I)
D: Engine for use in dust-atmosphere (Group III)

When used in Group II, no letter is used here. |
| 3 - 4 | Without influence on explosion protection (Number of poles) |

15.2 **Description**

The enclosures of the flameproof electric motors are made of cast iron and have a mounting place for terminal boxes.

The shaft will be fixed with ball bearings or cylindrical roller bearings.

A terminal compartment in type of protection Flameproof enclosure "d" or Increased safety "e" or a direct cable entry is used for electrical connection of the motor. For electric power input into the motor compartment, separately certified cable glands or conductor bushings are used.

The cooling of the motor is realised by an external fan that is made of steel (Group I and Group II) or aluminium (Group II and Group III). The fan is driven by the electrical machine itself.

Optionally a space heater can be mounted inside the stator housing.

For direct temperature monitoring the winding of the motor is equipped with temperature sensors (thermistors according DIN 44081 respectively DIN 44082). The sensors are connected in series. Additional Pt0 or Pt100 can be installed in winding.

Optionally the temperature at the bearings could be monitored separately certified resistance thermometers (Pt100).

The sensors or the thermometers shall be connected to a trigger unit which is certified for this purpose.

The maximum permissible ambient temperatures are -50 °C to +60 °C. This temperature range may be limited as a result of the selected terminal boxes and components, or the electrical design. If the motor is converter-fed the converter must be of type voltage-source converter with pulse width modulation.

15.3 Parameters

15.3.1 Electrical parameters

15.3.1.1 Circuits of the flameproof electric motors

Rated voltage ¹			
5KT** 250 */* (without 5KTC R 250 */*)	up to	690	V AC
5KTCR 250 */*	up to	1100	V AC
Rated rotational speed	500	up to	3600 min ⁻¹
Rated rotational speed (with converter)	150	up to	5800 min ⁻¹
Frequency (mains)			50 / 60 Hz
Frequency (converter)	5	up to	87 Hz
Duty type	S1	to	S9

Rated power			
Frame size			
250	up to	66	kW

¹ In case of converter-fed: Voltage of the fundamental wave measured at the motor terminals. This voltage must not be decreased by 10 %, taken into account the minimum converter input voltage and the voltage drop caused by the supply line and an optional sinus filter.

15.3.1.2 Electrical parameters (voltage-source converter)

Maximum permitted input voltage	Rated voltage of the motor	V
Minimum switching frequency	1.2	kHz
Current limiting value	$1.5 \times I_N$	
Maximum overload time / Time for operation below minimum frequency ²	60	s
Output frequency	up to 87	Hz

² The maximum overload time and the permitted time for operation below the minimum output frequency are in relation with a period of 10 minutes.

15.3.1.3 Monitoring circuit

Temperature sensors (ptc thermistors)

According to the specifications given in the certificate of the trigger unit and the electrical design.

Circuits of the resistance thermometer (Pt100)

According to the specifications given in the certificate of the trigger unit and the electrical design.

15.3.2 Thermal ratings

Permitted ambient temperature range			
Group II Ex db	Group II Ex db eb	Group III Ex tb	Group I Ex db / Ex db eb
$-50\text{ °C} \leq T_a \leq +60\text{ °C}$	$-20\text{ °C} \leq T_a \leq +60\text{ °C}$	$-25\text{ °C} \leq T_a \leq +60\text{ °C}$	$-25\text{ °C} \leq T_a \leq +60\text{ °C}$

The temperature class and the surface temperature are determined by a routine test of the manufacturer considering the ambient temperature range and the electrical variant.

16 **Report Number**

BVS PP 18.2053 EU, as of 2018-04-17

17 **Special Conditions for Use**

- 17.1 The lengths of the flameproof joints are in parts longer and the gaps of the flameproof joints are in parts smaller than the values of table 2 and 3 of EN 60079-1:2014. For information of the dimensions of the flameproof joints contact the manufacturer.
- 17.2 Fasteners with a minimum yield stress of 640 N/mm² must be used for the closing of the flameproof enclosure.
- 17.3 Motors which have to be equipped with a direct temperature control must be monitored by a separate certified trigger unit.
- 17.4 Before setting-up operation it has to be ensured that no inadmissible over voltage caused by converter supply may occur at the terminals of the motor. Clearances and creepage distances inside the terminal box do not permit an overvoltage cause by the converter which increase:
 - 3.1 x U_N for rated voltages ≤ 600 V
 - 2.04 x U_N for rated voltages > 600 V and ≤ 1100 VThe insulating system of the motor may require an additional limitation of a periodic over voltage.

18 **Essential Health and Safety Requirements**

The Essential Health and Safety Requirements are covered by the standards listed under item 9.

19 **Drawings and Documents**

Drawings and documents are listed in the confidential report.

We confirm the correctness of the translation from the German original.
In the case of arbitration only the German wording shall be valid and binding.

DEKRA EXAM GmbH
Bochum, dated 2018-04-17
BVS-Wlo/Nu A 20150508



Certifier



Approver